
The Pipeline - Edition 9





CERROWIRE



THHN/THWN-2

Thermoplastic-insulated copper wire with a nylon covering.

Sizes 8 AWG through 1000 kcmil feature Cerrowire SLiPWire® Technology for fast and easy pulling in conduit.


This 90°C, 600 volt building wire is for use in residential, commercial and industrial applications.



- Branch circuit wiring
- Ceiling fans
- Dry locations only
- Receptacles
- Residential




PRODUCT FEATURES











SERVICEWIRE

- <u>ServiceDrive[®] Tray Selection Guide</u>
- ServiceDrive® MC Selection Guide
- ServiceDrive®—Protects Against Costly Downtime, Diagnosis, and Repair

VFD TRAY CABLE RHW-2/PVC, Shielded 2,000 Volt Copper



conductors, stranded

and insulated with heat

and moisture resistant,

chemically crosslinked

and cabled together

with suitable fillers and

three symmetrical bare

polyethylene (type

copper ground

conductors.

Three copper

VFD TERMINATING CONNECTOR for Direct Wiring (Tray) 2,000 Volt Copper



Patented connectors for direct wiring installations are designed exclusively to terminate VFD tray RHW-2), phase identified cables in control centers, panel boards, junction boxes, motors, and motor control enclosures.

VFD TERMINATION KIT

for Tray or MC Cable 600/1,000/2,000 Volt Copper



Flat tinned copper braid with woven tinned copper construction, stainless steel spring clamp, and adhesive-backed copper foil tape (shields against EMI/RFI radiation), which is conductive through the adhesive.

TF KABLE



MV-105 5kV/15kV

APPLICATIONS

INDUSTRIAL AND COMMERCIAL

- Chemical Plants
- Petrochemical Plants
- Electrical Utility Plants
- Water Treatment Facilities
- Textile Mills
- Steel Mills
- Paper Mills
- Airports
- Shopping Malls
- Military Bases
- Medical Facilities
- Sports Stadiums

INSTALLATIONS

- In Cable Tray
- Conduit in Air
- Aerial with Messenger Supported
- Direct Buried
- Underground Duct
- Wet and Dry Locations

SOURCERY WIRE & CABLE



- Point to Point Cables
- Break Out Cables
- Spider Cables
- Cross-Laced, Taped, Spiral Wrapped
- Parallel Custom Cables
- UL Listed

SPIRAL

CROSS LACED

QUICK RELEASE







BREAKOUT

PARALLEL

SPIDER








KINGWIRE

XHHW-2 ALUMINUM CONDUCTOR

Compact stranded 8000 Series aluminum alloy conductor. Insulation is an abrasion, moisture, heat and sunlight resistant black cross-linked polyethylene.







Type MC cable is constructed with 3 or 4 8000 series compact stranded aluminum XHHW-2 conductors cabled with a bare or insulated 8000 series aluminum grounding conductor. A binder identification baring tape is wrapped



over the cabled assembly. Aluminum armor is interlocked over the conductor assembly. All insulated conductors are phase identified.

For questions regarding these any of these products, please call our office 314-524-4424 or email your salesperson:

Brian Greenwald bgreenwald@meglio.com
Dave Meglio dmeglio@meglio.com
Ed Snyder esnyder@meglio.com
Eric Ripp eripp@meglio.com
Jason Kyle jkyle@meglio.com
Jordan Buck jbuck@meglio.com
Mike Meglio mmeglio@meglio.com
Nick Frederking nfrederking@meglio.com
TJ Frederking tfrederking@meglio.com

Employee Spotlight

JOHN MEGLIO



John started working at Meglio in 1985. He started out selling industrial products. Now, he sells ABB Switchgear and automatic transfer switches. When John is not working, he enjoys being Mr. Fix It around the house, hiking and reading / watching crime novels / movies. We appreciate the 25 years of commitment John has given to Meglio & Associates and the interesting stories he has gathered along the way!!

Tell us about a Meglio employee that went above and beyond & be entered to win one of five \$25 Visa Giftcards.

Email response to Teresa Vitale, tvitale@meglio.com

